

Minarc Evo

MORE POWERFUL AND AFFORDABLE THAN EVER BEFORE



TECHNICAL SPECIFICATIONS

Minarc Evo 180

Product code	61002180
Connection voltage 1~ 50/60 Hz	230 V ±15 %
Fuse (delayed)	16 A
Minimum generator power	5.5 kVA
Output (40°C) TIG	100 % ED, 130 A / 15.2 V 35 % ED, 180 A / 17.2 V
Output (TIG) 35% ED	180 A/17.2 V
Output (TIG) 60% ED	150 A / 15 V
Output (TIG) 100% ED	130 A/15.2 V
Output (MMA) 30% ED	170 A/26.8 V (140AU: 28% ED 140 A/25.6 V)
Output (MMA) 60% ED	140 A / 25.6 V
Output (MMA) 100% ED	115 A/24.6 V (140AU: 80 A/23.2 V)
Open circuit voltage	90 V
Stick electrode sizes	1.5...4.0 mm
Welding range (MMA)	10 A/15 V - 170 A/32 V
Welding range (TIG)	10 A/10 V - 180 A/30 V
Rated power at max. current 30% ED MMA	170 A / 5.7 kVA
Rated power at max. current 35% ED TIG	180 A / 4.0 kVA
Power factor at 100 % ED	0.99
Efficiency at 100 % ED (MMA)	84 %
External dimensions LxWxH	361 x 139 x 267 mm
Weight (no accessories)	5.4 kg
Degree of protection	IP23S
Standards	IEC 60974-1 IEC 60974-10 IEC 61000-3-12
Weight (with connection cable)	5.85 kg
EMC class	A
Norms	IEC 60974-1, -10, IEC 61000-3-12
Operating temperature range	-20...+40 °C



Minarc Evo 180 AU

Product code	61002180AU
Connection voltage 1~ 50/60 Hz	230 V ±15 %
Fuse (delayed)	16 A
Minimum generator power	5.5 kVA
Output (TIG) 35% ED	180 A/17.2 V
Output (TIG) 100% ED	130 A/15.2 V
Output (MMA) 30% ED	170 A/26.8 V
Output (MMA) 100% ED	115 A/24.6 V
Open circuit voltage	12 V
Stick electrode sizes	1.5...4.0 mm
Welding range (MMA)	10 A/10 V - 180 A/30 V 10 A/15 V - 170 A/32 V
Rated power at max. current 30% ED MMA	170 A/5.7 kVA
Rated power at max. current 35% ED TIG	180 A/4.0 kVA
External dimensions LxWxH	361 × 139 × 267 mm
Weight (no accessories)	5.4 kg
Degree of protection	IP23S
Standards	IEC 60974-1 IEC 60974-10 IEC 61000-3-12
Operating temperature range	-20...+40 °C

Minarc Evo 180 DK

Product code	61002180DK
Connection voltage 1~ 50/60 Hz	230 V ±15 %
Fuse (delayed)	16 A
Minimum generator power	5.5 kVA
Output (TIG) 35% ED	180 A/17.2 V
Output (TIG) 100% ED	130 A/15.2 V
Output (MMA) 30% ED	170 A/26.8 V
Output (MMA) 100% ED	115 A/24.6 V
Open circuit voltage	12 V
Stick electrode sizes	1.5...4.0 mm
Welding range (MMA)	10 A/10 V - 180 A/30 V 10 A/15 V - 170 A/32 V
Rated power at max. current 30% ED MMA	170 A/5.7 kVA
Rated power at max. current 35% ED TIG	180 A/4.0 kVA
External dimensions LxWxH	361 × 139 × 267 mm
Weight (no accessories)	5.4 kg
Degree of protection	IP23S
Standards	IEC 60974-1 IEC 60974-10 IEC 61000-3-12
Operating temperature range	-20...+40 °C



Minarc Evo 180 VRD

Product code	61002180VRD
Connection voltage 1~ 50/60 Hz	230 V ±15 %
Fuse (delayed)	16 A
Minimum generator power	5.5 kVA
Output (MMA)	115 A/24.6 V (100 %) 170 A/26.8 V (30 %)
Output (TIG)	130 A/15.2 V (100 %) 180 A/17.2 V (35 %)
Open circuit voltage	30 V
Stick electrode sizes	1.5...4.0 mm
Welding range (MMA)	10 A/15 V – 170 A/32 V
Welding range (TIG)	10 A/10 V – 180 A/30 V
External dimensions LxWxH	361 × 139 × 267 mm
Weight (no accessories)	5.4 kg
Degree of protection	IP23S
Standards	IEC 60974-1 IEC 60974-10 IEC 61000-3-12
Operating temperature range	-20...+40 °C

Minarc Evo 140 AU

Product code	61002140AU
Connection voltage 1~ 50/60 Hz	230 V ±15 %
Fuse (delayed)	10 A
Minimum generator power	5.5 kVA
Output (MMA) 28% ED	140 A/25.6 V (28 %)
Output (MMA) 100% ED	80 A/23.2 V
Open circuit voltage	12 V
Stick electrode sizes	1.5...3.25 mm
Welding range (MMA)	10A/15V - 140A/38V
Welding range (TIG)	10A/1V - 150A/37V
External dimensions LxWxH	361 × 139 × 267 mm
Weight (no accessories)	5.4 kg
Degree of protection	IP23S
Standards	IEC 60974-1 IEC 60974-10 IEC 61000-3-12
Operating temperature range	-20...+40 °C

ACCESSORIES

Earth return cable 5 m, 16 mm²

Product code	6184015
--------------	---------



Welding cable 5 m 16 mm²

Product code	6184005
--------------	---------

Shoulder strap

Product code	9592163
--------------	---------

Remote control R10

Product code	R10, 5 m - 6185409 R10, 10 m - 618540901
--------------	---

TX 163GVD9

Product code	TX163GVD94 (4m)
Standards	IEC 60974-7
Type of cooling	Gas
Type of connection (Current-gas)	DIX 9 mm
Load capacity @ 40 % (Argon)	160 A
Load capacity @ 100 % (Argon)	-
Type of connection (Control)	-
Type of connection (Coolant)	-
Remote control	No
Neck type	70° angle

WWW.KEMPPI.COM

Kemppi is the design leader in the arc welding industry. We are committed to boosting the quality and productivity of welding by continuous development of the welding arc and by working for a greener and more equal world. Kemppi supplies sustainable products, digital solutions, and services for professionals from industrial welding companies to single contractors. The usability and reliability of our products is our guiding principle. We operate with a highly skilled partner network covering over 70 countries to make its expertise locally available. Headquartered in Lahti, Finland, Kemppi employs close to 800 professionals in 16 countries and has a revenue of 195 MEUR in 2022.

