Gamma GTH3 XFA



BENEFITS

- Meets the highest European classification for respiratory performance (TH3) and the defined standards for Australia and New Zealand (P2).
- Integrated LED working lights improve safety and work efficiency in dimly lit welding conditions.
- Class leading LiFE+ Color Auto-darkening welding filter makes working more convenient with extended shade selection up to level 15.
- Visible welding filter parameter selection enables working without interruptions when settings can be adjusted on the go with the remote control.
- GapView switch sets a clear view beneath the welding visor providing a 15 mm gap and a clear vision of the working area.
- · Axis regulator tunes eye-line perspective.
- Heavy duty battery charged full in only 3 hours.
- 198 cm² grinding visor, 170° work site view.
- Respirator (PFU 210e) air speed selection 170 or 210 liters per minute.
- Features for added comfort and safety such as a flexible and adjustable headband, axis regulator to adjust the visor position and ClickLenz system allowing the replacement of clear lens plates in seconds.

OVERVIEW

Gamma GTH3 XFA offers top class safety and comfort with total freedom of movement. Even in the toughest working environments, Gamma GTH3 XFA is the ultimate welder's respirator, featuring class leading LiFE+ Color ADF, integrated LED work lights, fast charge Liion battery packs and all Gamma comfort features.

TECHNICAL SPECIFICATIONS

Gamma GTH3 XFA

| Product code | P0721 |
|-----------------------|------------------|
| Weight | 1100 g |
| Operating temperature | -5+55 °C <80% Rh |
| EN 175 | В |
| EN 12941 | TH3 |
| AS/NZS 1716 | P2 |
| Welding filter | XA 74 |
| View size | 102 x 74 mm |
| Filter dimension | Customized |

Gamma GTH3 XFA

| Shade range | 5, 8, 9-15 |
|----------------------------|------------|
| ADF light state | 4 |
| ADF CE Classification | 1/1/1/2 |
| ADF switching time | 0.1 ms |
| LiFE+ Color (yes/no) | Yes |
| Grinding function (yes/no) | No |
| PAPR | PFU 210e |

27072024 27072024