

# Master M 358 GM



## OVERVIEW

MIG/MAG welder with manual, synergic (Auto), pulse (Auto Pulse), and double pulse welding options. Provides 350 A with a 40% duty cycle. Intelligent welding parameter setting with Weld Assist. Full-color TFT display with integrated digital connectivity to WeldEye and LED work lights for excellent user experience. Includes work pack welding software programs inc. Fe, Ss, Al, CuSi, CuAl, Fe Metal, Fe Rutil, FC-CrNiMo materials. Generator and multi-voltage use.

## TECHNICAL SPECIFICATIONS

### Master M 358 GM

Product code	MSM358GM
Connection voltage 3~ 50/60 Hz	380 - 460 V $\pm 10$ %; 220 - 230 V $\pm 10$ %
Fuse	16/32 A
Output 40% ED	350 A (MMA 330 A); 300 A (MMA 280 A)
Output 60% ED	280 A; 240 A
Output 100% ED	220 A; 190 A
Wire feed mechanism	4-roll, single-motor
Wire feed speed	0.5 - 25 m/min
Rated power at max. current	14 kVA
Recommended generator power (min)	20 kVA
Gun connection	Euro
Wire spool weight, max.	20 kg
Wire spool diameter, max.	300 mm
Filler wires, Ss	0.8 - 1.2 mm
Filler wires, Al	0.8 - 1.2 mm
Filler wires, Fe	0.8 - 1.2 mm
Filler wires, MC/FC	0.8 - 1.2 mm

**Master M 358 GM**

Diameter of feed rolls	32mm
Welding current and voltage range, MIG	15 A/10 V - 350 A/ 45 V; 15 A/10 V - 300 A/ 40 V
Welding current and voltage range, TIG	15 A/1 V - 350 A/ 45 V; 15 A/1 V - 300 A/ 40 V
Welding current and voltage range, MMA	15 A/10 V - 330 A/ 45 V; 15 A/10 V - 280 A/ 40 V
Shielding gas pressure (max)	0.5 MPa
External dimensions LxWxH	602 x 298 x 447 mm
Weight (no accessories)	27 kg
Degree of protection	IP23S
Standards	IEC 60974-1, -10
EMC class	A
Operating temperature range	-20...+40 °C
Storage temperature range	-40...+60 °C