

# X3 Wire Feeder HD300



## OVERVIEW

Side-loading wire feeder for all X3 FastMig power sources with a digital LCD display. 4-wheel wire feed mechanism, safe-lift design, and integrated storage for parts in the side door. The robust plastic case with dual wall construction has been designed to absorb knocks and bangs during heavy welding fabrication applications. A plastic rotating plate is delivered with the X3 Wire Feeder HD300.

## TECHNICAL SPECIFICATIONS

### X3 Wire Feeder HD300

Product code	X3HD300
Wire feed mechanism	4-roll, single-motor
Wire feed speed	0.5 ... 25 m/min
Gun connection	Euro
Wire spool weight, max.	20 kg
Wire spool diameter, max.	300 mm
Filler wires	Fe 0.8 ... 2.0 mm, Ss 0.8 ... 2.0 mm, MC/FC 0.8 ... 2.4 mm, Al 0.8 ... 2.4 mm
Diameter of feed rolls	32 mm
Shielding gas pressure (max)	0.5 MPa
Welding current, 60 %	450 A
Welding current, 100 %	380 A
External dimensions LxWxH	670 x 240 x 465 mm
Weight (no accessories)	14.4 kg
Degree of protection	IP23
Standards	IEC 60974-5, 10
EMC class	A
Operating temperature range	-20...+40 °C

**X3 Wire Feeder HD300**

Storage temperature range

-40...+60 °C