

X5 Wire Feeder 300 AP



OVERVIEW

Top-loading wire feeder with a graphical, 5.7" TFT display panel. For synergic and pulse MIG/MAG, TIG, stick (MMA), and gouging. Automatic parameter adjustment with Weld Assist. 4-wheel wire feed mechanism with integrated lighting and a kinetic spool brake, rotameter included as standard. USB port connectivity. Enables the use of MAX welding processes, Wise welding processes, and SuperSnake GTX sub feeder.

TECHNICAL SPECIFICATIONS

X5 Wire Feeder 300 AP

Product code	X5240300000
Wire feed mechanism	4-roll, single-motor
Wire feed speed	0.5 ... 25 m/min
Gun connection	Euro
Wire spool weight, max.	20 kg
Wire spool diameter, max.	300 mm
Filler wires	Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm
Diameter of feed rolls	32 mm
Shielding gas pressure (max)	0.5 MPa
Welding current, 60 %	500 A
Welding current, 100 %	430 A
External dimensions LxWxH	650 x 230 x 410 mm
Weight (no accessories)	10.9 kg
Degree of protection	IP23S
EMC class	A
Operating temperature range	-20...+40 °C
Storage temperature range	-40...+60 °C