

# X5 Wire Feeder 300 APC



## OVERVIEW

Top-loading wire feeder with a graphical, 5.7" TFT display panel. For synergic and pulse MIG/MAG, TIG, stick (MMA), and gouging. Automatic parameter adjustment with Weld Assist. 4-wheel wire feed mechanism with integrated lighting and a kinetic spool brake, rotameter included as standard. Embedded connectivity to WLAN, supporting the digital WPS and WeldEye ArcVision module. USB port connectivity. Enables the use of MAX welding processes, Wise special processes, SuperSnake GTX sub feeder, and HR45 remote control.

## TECHNICAL SPECIFICATIONS

### X5 Wire Feeder 300 APC

Product code	X5250300000
Wire feed mechanism	4-roll, single-motor
Wire feed speed	0.5 ... 25 m/min
Gun connection	Euro
Wire spool weight, max.	20 kg
Wire spool diameter, max.	300 mm
Filler wires	Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm
Diameter of feed rolls	32 mm
Operating temperature range	-20...+40 °C
External dimensions LxWxH	650 x 230 x 410 mm
Weight (no accessories)	10.9 kg
Degree of protection	IP23S
EMC class	A
Storage temperature range	-40...+60 °C
Shielding gas pressure (max)	0.5 MPa
Welding current, 60 %	500 A

**X5 Wire Feeder 300 APC**

Welding current, 100 %

430 A