

# X5 Wire Feeder HD300 M



## OVERVIEW

Side-loading wire feeder with a digital parameter display. For MIG/MAG, MMA, and gouging. Manual, 2-knob parameter control. 4-wheel wire feed mechanism with integrated lighting and a kinetic spool brake. Impact-resistant cabinet. USB port connectivity. Cabinet lights and LED work lights for excellent user experience. Enables the use of SuperSnake GTX sub feeder and HR45 remote control.

## TECHNICAL SPECIFICATIONS

### X5 Wire Feeder HD300 M

Product code	X5260300000
Wire feed mechanism	4-roll, single-motor
Wire feed speed	0.5 ... 25 m/min
Gun connection	Euro
Wire spool weight, max.	20 kg
Wire spool diameter, max.	300 mm
Filler wires	Fe 0.8 ... 2.0 mm Ss 0.8 ... 2.0 mm Mc/Fc 0.8 ... 2.4 mm Al 0.8 ... 2.4 mm
Diameter of feed rolls	32 mm
Shielding gas pressure (max)	0.5 MPa
Welding current, 60 %	500 A
Welding current, 100 %	430 A
External dimensions LxWxH	670 x 240 x 465 mm
Weight (no accessories)	14.4 kg
Degree of protection	IP23S
EMC class	A
Operating temperature range	-20...+40 °C
Storage temperature range	-40...+60 °C