

# X8 Power Source 600



## OVERVIEW

Provides 600 A with 40% duty cycle. Control Pad and X8 Cooler always included with the power source.

## TECHNICAL SPECIFICATIONS

### X8 Power Source 600

Product code	X8100601000 (Incl. X8 Control Pad and X8 Cooler) Power upgrade 600 for X8 Power Source - X8560000
Connection voltage 3~ 50/60 Hz	380 - 460 V $\pm 10$ % 380 - 460 V $\pm 10$ %
Fuse	35 A
Open circuit power (MMA) (without cooler and wire feeder, fans OFF)	44 - 53 W
Open circuit power (MMA) (without cooler and wire feeder, fans ON)	107 - 111 W
Open circuit power (MMA) (with cooler, without wire feeder, fans ON)	132 - 137 W
Output 40% ED	600 A
Output 60% ED	530 A
Output 100% ED	440 A
Welding current and voltage range, MIG @ 380 V	10A/10V - 600A/57V
Welding current and voltage range, MMA @ 380 V	10A/10V - 600A/58,5V
Recommended generator power (min)	40 kVA
Open circuit voltage MMA	50 V
External dimensions LxWxH	921 x 348 x 795 mm
Weight (no accessories)	95 kg
Operating temperature range	-20...+40 °C