

MinarcTig Evo 200



CARACTERÍSTICAS TÉCNICAS

MinarcTig Evo 200

Código de producto	MinarcTig Evo 200, TX 225G 4M – P0640TX MinarcTig Evo 200, TX 225G 8M – P0641TX MinarcTig Evo 200, TX 225GS 8M – P0645TX MinarcTig Evo 200, TX 165GS 4M – P0648TX MinarcTig Evo 200, TX 165GS 8M – P0649TX MinarcTig Evo 200, TX 135GF 4M – P0652TX MinarcTig Evo 200, TX 135GF 8M – P0653TX MinarcTig Evo 200, TX 165GF 4M – P0656TX MinarcTig Evo 200, TX 165GF 8M – P0657TX MinarcTig Evo 200, TX 225GS 4M – P0644TX MinarcTig Evo 200, TX 165GS 16M – P0670TX MinarcTig Evo 200, TX 305WF 4M, COOLER – P0676TX MinarcTig Evo 200, TX 305WF 8M, COOLER – P0677TX MinarcTig Evo 200, TX 255WS 4M, COOLER – P0687TX MinarcTig Evo 200, TX 255WS 8M, COOLER – P0688TX MinarcTig Evo 200, TX 355W 4M, COOLER – P0691TX MinarcTig Evo 200, TX 355W 8M, COOLER – P0692TX
Voltaje de conexión 1~ 50/60 Hz	230 V ±15%
Fusible (retardado)	16 A
Potencia mínima del generador	5,6 kVA
Salida (TIG) 35 % ED	200 A/18,0 V (35%)
Salida (TIG) 60 % ED	160 A/16,4 V (60%)
Salida (TIG) 100 % ED	140 A/15,6 V (100%)
Salida (MMA) 35 % ED	170 A/26,8 V (35%)
Salida (MMA) 60 % ED	130 A/25,2 V (60%)
Salida (MMA) 100 % ED	110 A/24,4 V (100%)
Voltaje en vacío	95 V
Tamaños de electrodo de varilla	1,5-4,0 mm
Rango de soldadura (MMA)	10 A /20,4 V...170 A/26,8 V

MinarcTig Evo 200

Rango de soldadura (TIG)	5 A/10,2 V...200 A/18,0 V
Rango temperatura de operación	-20...+40 °C
Dimensiones externas L x A x A	449 × 210 × 358 mm
Peso (sin accesorios)	11 kg
Grado de protección	IP23S
Normas	IEC 60974-1, IEC 60974-3, IEC 60974-10, IEC 61000-3-12