

X8 Power Source 400



DESCRIPCIÓN GENERAL

Provides 400 A with a 60% duty cycle. Can be ordered with or without X8 Cooler. Control Pad always included with the power source.

CARACTERÍSTICAS TÉCNICAS

X8 Power Source 400

Código de producto	X8100400001 - X8 Power Source 400, CUSTOM (Work Pack + WiseFusion) X8100401000 - X8 Power Source 400, cooler X8100401001 - X8 Power Source 400, cooler, CUSTOM (Work Pack + WiseFusion)
Voltaje de conexión 3~ 50/60 Hz	380 - 460 V \pm 10 %
Fusible	32 A
Potencia de circuito abierto (MMA) (sin refrigerador ni alimentador de alambre, ventiladores OFF)	44 - 53 W
Potencia de circuito abierto (MMA) (sin refrigerador ni alimentador de alambre, ventiladores ON)	107 - 111 W
Potencia de circuito abierto (MMA) (con refrigerador, sin alimentador de alambre, ventiladores ON)	132 - 137 W
Salida 60 % ED	400 A
Salida 100 % ED	320 A
Rango de corriente y voltaje de soldadura, MIG a 380 V	20A/14V - 400A/50V
Rango de corriente y voltaje de soldadura, MMA a 380 V	15A/20V - 400A/58V
Potencia recomendada del generador (mín.)	25 kVA
Voltaje en vacío (MMA)	50 V
Dimensiones externas L x A x A	921 x 348 x 795 mm
Peso (sin accesorios)	95 kg
Rango temperatura de operación	-20...+40 °C