

# X8 Power Source 500 MV



## OVERSIKT

Provides 500 A with a 60% duty cycle. The multi-voltage power source is suitable for the most common electrical network voltages. Control Pad and X8 Cooler always included with the power source.

## TEKNISKE SPESIFIKASJONER

### X8 Power Source 500 MV

Produktkode	X8100501100 - X8 Power Source 500 MV, cooler X8100501101 - X8 Power Source 500 MV, cooler, CUSTOM (Work Pack + WiseFusion)
Strømtilkoblingsspenning 3- 50/60 Hz	220 - 230 V $\pm 10$ % 380 - 460 V $\pm 10$ %
Sikring	32 A
Sikring, 380 – 460 V	63 A
Åpen krets-strøm (MMA) (uten kjøler og trådmater, vifter AV)	44 - 53 W
Åpen krets-strøm (MMA) (uten kjøler og trådmater, vifter PÅ)	99 - 111 W
Åpen krets-strøm (MMA) (med kjøler, uten trådmater, vifter PÅ)	121 - 137 W
Ytelse 60 % ED	500 A
Ytelse 100 % ED	400 A
Sveisestrøm og spenningsområde, MIG @ 220 V	20A/14V - 500A/55V
Sveisestrøm og spenningsområde, MIG @ 380 V	20A/14V - 500A/55V
Sveisestrøm og spenningsområde, MMA @ 220 V	15A/20V - 500A/57V
Sveisestrøm og spenningsområde, MMA @ 380 V	15A/20V - 500A/57V
Anbefalt generatorstrøm (min)	35 kVA
Åpen krets-spenning (MMA)	50 V
Utvendige mål LxBxH	921 x 348 x 795 mm
Vekt (uten tilbehør)	95 kg

**X8 Power Source 500 MV**

Driftstemperaturområde

-20...+40 °C