

MinarcTig 250



TEKNISKA DATA

MinarcTig 250

Produktkod	MinarcTig 250, TX 165GF 4M – P0607TX MinarcTig 250, TX 165GF 8M – P0608TX MinarcTig 250, TX 225G 4M – P0609TX MinarcTig 250, TX 225G 8M – P0610TX MinarcTig 250, TX 165GS 4M – P0625TX MinarcTig 250, TX 165GS 8M – P0626TX MinarcTig 250, TX 225GS 4M – P0632TX MinarcTig 250, TX 225GS 8M – P0633TX MinarcTig 250, TX 135GF 4M – P0636TX MinarcTig 250, TX 135GF 8M – P0637TX MinarcTig 250, TX 165GS 16M – P0668TX
Anslutningsspänning 3-fas 50/60 Hz	400 V -20...+15 %
Säkring (trög)	10 A
Uteffekt (TIG) 30% ED	250 A/20,1 V (30 %)
Uteffekt (TIG) 100 % ED	160 A/16,4 V (100 %)
Uteffekt (MMA) 35% ED	220 A/ 28,8 V (35 %)
Uteffekt (MMA) 100 % ED	150 A/26,0 V (100 %)
Tomgångsspänning	95 V (VRD 30 V)
Elektrodstorlekar	1,5...5,0 mm
Svetsområde (MMA)	10 A/20,4 V-220 A/28,8 V
Svetsområde (TIG)	5 A/10,2 V-250 A/20,1 V
Yttermått L × B × H	400 × 180 × 340 mm
Vikt (inga tillbehör)	11 kg (utan kablar)
Skyddsklass	IP23S
Omgivningstemperatur	-20...+40 °C