

MinarcTig Evo 200



TEKNISKA DATA

MinarcTig Evo 200

Produktkod	MinarcTig Evo 200, TX 225G 4M – P0640TX MinarcTig Evo 200, TX 225G 8M – P0641TX MinarcTig Evo 200, TX 225GS 8M – P0645TX MinarcTig Evo 200, TX 165GS 4M – P0648TX MinarcTig Evo 200, TX 165GS 8M – P0649TX MinarcTig Evo 200, TX 135GF 4M – P0652TX MinarcTig Evo 200, TX 135GF 8M – P0653TX MinarcTig Evo 200, TX 165GF 4M – P0656TX MinarcTig Evo 200, TX 165GF 8M – P0657TX MinarcTig Evo 200, TX 225GS 4M – P0644TX MinarcTig Evo 200, TX 165GS 16M – P0670TX MinarcTig Evo 200, TX 305WF 4M, COOLER – P0676TX MinarcTig Evo 200, TX 305WF 8M, COOLER – P0677TX MinarcTig Evo 200, TX 255WS 4M, COOLER – P0687TX MinarcTig Evo 200, TX 255WS 8M, COOLER – P0688TX MinarcTig Evo 200, TX 355W 4M, COOLER – P0691TX MinarcTig Evo 200, TX 355W 8M, COOLER – P0692TX
Anslutningsspänning 1-fas, 50/60 Hz	230 V ±15 %
Säkring (trög)	16 A
Elverk, min. effekt	5,6 kVA
Uteffekt (TIG) 35% ED	200 A/18,0 V (35 %)
Uteffekt (TIG) 60% ED	160 A/16,4 V (60 %)
Uteffekt (TIG) 100 % ED	140 A/15,6 V (100 %)
Uteffekt (MMA) 35% ED	170 A /26,8 V (35 %)
Uteffekt (MMA) 60% ED	130 A/25,2 V (60 %)
Uteffekt (MMA) 100 % ED	110 A/24,4 V (100 %)
Tomgångsspänning	95 V
Elektrodstorlekar	1,5...4,0 mm
Svetsområde (MMA)	10 A /20,4 V...170 A/26,8 V

MinarcTig Evo 200

Svetsområde (TIG)	5 A/10,2 V...200 A/18,0 V
Yttermått L × B × H	449 × 210 × 358 mm
Vikt (inga tillbehör)	11 kg
Skyddsklass	IP23S
Standarder	IEC 60974-1, IEC 60974-3, IEC 60974-10, IEC 61000-3-12
Omgivningstemperatur	-20...+40 °C