

MinarcTig Evo 200



技术规格

MinarcTig Evo 200

产品代码	MinarcTig Evo 200, TX 225G 4米 - P0640TX MinarcTig Evo 200, TX 225G 8米 - P0641TX MinarcTig Evo 200, TX 225GS 8米 - P0645TX MinarcTig Evo 200, TX 165GS 4米 - P0648TX MinarcTig Evo 200, TX 165GS 8米 - P0649TX MinarcTig Evo 200, TX 135GF 4米 - P0652TX MinarcTig Evo 200, TX 135GF 8米 - P0653TX MinarcTig Evo 200, TX 165GF 4米 - P0656TX MinarcTig Evo 200, TX 165GF 8米 - P0657TX MinarcTig Evo 200, TX 225GS 4米 - P0644TX MinarcTig Evo 200, TX 165GS 16米 - P0670TX MinarcTig Evo 200, TX 305WF 4米, COOLER - P0676TX MinarcTig Evo 200, TX 305WF 8米, COOLER - P0677TX MinarcTig Evo 200, TX 255WS 4米, COOLER - P0687TX MinarcTig Evo 200, TX 255WS 8米, COOLER - P0688TX MinarcTig Evo 200, TX 355W 4米, COOLER - P0691TX MinarcTig Evo 200, TX 355W 8米, COOLER - P0692TX
连接电压 1~ 50/60 Hz	230 V ± 15 %
保险丝 (延时)	16 A
发电机最小功率	5.6kVA
输出 (TIG) 35 % 暂载率	200 A/18.0 V (35 %)
输出 (TIG) 60 % 暂载率	160 A/16.4 V (60%)
输出 (TIG) 100 % 暂载率	140 A/15.6 V (100 %)
输出 (MMA) 35 % 暂载率	170 A/26.8 V (35 %)
输出 (MMA) 60 % 暂载率	130 A/25.2 V (60 %)
输出 (MMA) 100 % 暂载率	110 A/24.4 V (100 %)
开路电压	95 V
电焊条尺寸	1.5...4.0 mm
焊接范围 (MMA)	10 A /20.4 V...170 A/26.8 V

MinarcTig Evo 200

焊接范围 (TIG)	5 A/10.2 V...200 A/18.0 V
外部尺寸 (长 x 宽 x 高)	449 × 210 × 358 mm
重量 (无配件)	11 公斤
保护等级	IP23S
标准	IEC 60974-1, IEC 60974-3, IEC 60974-10, IEC 61000-3-12
工作温度范围	-20...+40 °C