

X8 Power Source 400 MV



概览

Provides 400 A with a 60% duty cycle. The multi-voltage power source is suitable for the most common electrical network voltages. Control Pad always included with the power source. X8 Cooler not included.

技术规格

X8 Power Source 400 MV

产品代码	X8100400101 - X8 Power Source 400 MV, CUSTOM (Work Pack + WiseFusion)
电源连接电压 3~ 50/60 Hz	220 - 230 V \pm 10 % 380 - 460 V \pm 10 %
保险丝	32 A
保险丝, 380 - 460 V	63 A
空载功率 (MMA) (不带冷却器和送丝机, 风扇关闭)	44 - 53 W
空载功率 (MMA) (不带冷却器和送丝机, 风扇打开)	99 - 111 W
输出 60% ED	400 A
输出 100% 暂载率	320 A
焊接电流和电压范围, MIG @ 220 V	20 A/14 V - 400 A/50 V
焊接电流和电压范围, MIG @ 380 V	20 A/14 V - 400 A/50 V
焊接电流和电压范围, MMA @ 220 V	15 A/20 V - 400 A/58 V
焊接电流和电压范围, MMA @ 380 V	15 A/20 V - 400 A/58 V
建议的发电机功率 (最小)	35 kVA
空载电压 (MMA)	50 V
外部尺寸 (长 x 宽 x 高)	921 x 348 x 795 mm
重量 (无配件)	95 kg
工作温度范围	-20...+40 °C