

# X8 Power Source 500 MV



## 概览

Provides 500 A with a 60% duty cycle. The multi-voltage power source is suitable for the most common electrical network voltages. Control Pad and X8 Cooler always included with the power source.

## 技术规格

### X8 Power Source 500 MV

产品代码	X8100501100 - X8 Power Source 500 MV, cooler X8100501101 - X8 Power Source 500 MV, cooler, CUSTOM (Work Pack + WiseFusion)
电源连接电压 3~ 50/60 Hz	220 - 230 V $\pm$ 10 % 380 - 460 V $\pm$ 10 %
保险丝	32 A
保险丝, 380 - 460 V	63 A
空载功率 (MMA) (不带冷却器和送丝机, 风扇关闭)	44 - 53 W
空载功率 (MMA) (不带冷却器和送丝机, 风扇打开)	99 - 111 W
空载功率 (MMA) (带冷却器, 不带送丝机, 风扇打开)	121 - 137 W
输出 60% ED	500 A
输出 100% 暂载率	400 A
焊接电流和电压范围, MIG @ 220 V	20A/14V - 500A/55V
焊接电流和电压范围, MIG @ 380 V	20A/14V - 500A/55V
焊接电流和电压范围, MMA @ 220 V	15A/20V - 500A/57V
焊接电流和电压范围, MMA @ 380 V	15A/20V - 500A/57V
建议的发电机功率 (最小)	35 kVA
空载电压 (MMA)	50 V
外部尺寸 (长 x 宽 x 高)	921 x 348 x 795 mm
重量 (无配件)	95 kg

X8 Power Source 500 MV

工作温度范围

-20…+40 °C