

X8 Power Source 600 MV



概览

Provides 600 A with a 40% duty cycle. The multi-voltage power source is suitable for the most common electrical network voltages. Requires a 63 A plug. Control Pad and X8 Cooler always included with the power source.

技术规格

X8 Power Source 600 MV

产品代码	X8100601100 (Incl. X8 Control Pad and X8 Cooler) Power upgrade 600 for X8 Power Source - X8560000
电源连接电压 3~ 50/60 Hz	220 - 230 V \pm 10 % 380 - 460 V \pm 10 %
保险丝, 380 - 460 V	35 A
空载功率 (MMA) (不带冷却器和送丝机, 风扇关闭)	44 - 53 W
空载功率 (MMA) (不带冷却器和送丝机, 风扇打开)	99 - 111 W
空载功率 (MMA) (带冷却器, 不带送丝机, 风扇打开)	121 - 137 W
输出 40% ED	600 A
输出 60% ED	530 A
输出 100% 暂载率	440 A
焊接电流和电压范围, MIG @ 220 V	10A/10V - 600A/47V
焊接电流和电压范围, MIG @ 380 V	10A/10V - 600A/57V
焊接电流和电压范围, MMA @ 220 V	10A/10V - 600A/47V
焊接电流和电压范围, MMA @ 380 V	10A/10V - 600A/58.5V
建议的发电机功率 (最小)	40 kVA
空载电压 (MMA)	50 V
外部尺寸 (长 x 宽 x 高)	921 x 348 x 795 mm
重量 (无配件)	95 kg

X8 Power Source 600 MV

工作温度范围	-20…+40 °C
保险丝, 220 - 230 V	63 A