

# X8 Power Source 600



## 概览

Provides 600 A with 40% duty cycle. Control Pad and X8 Cooler always included with the power source.

## 技术规格

### X8 Power Source 600

产品代码	X8100601000 (Incl. X8 Control Pad and X8 Cooler) Power upgrade 600 for X8 Power Source - X8560000
电源连接电压 3~ 50/60 Hz	380 - 460 V $\pm$ 10 % 380 - 460 V $\pm$ 10 %
保险丝	35 A
空载功率 (MMA) (不带冷却器和送丝机, 风扇关闭)	44 - 53 W
空载功率 (MMA) (不带冷却器和送丝机, 风扇打开)	107 - 111 W
空载功率 (MMA) (带冷却器, 不带送丝机, 风扇打开)	132 - 137 W
输出 40% ED	600 A
输出 60% ED	530 A
输出 100% 暂载率	440 A
焊接电流和电压范围, MIG @ 380 V	10A/10V - 600A/57V
焊接电流和电压范围, MMA @ 380 V	10A/10V - 600A/58,5V
建议的发电机功率 (最小)	40 kVA
空载电压 (MMA)	50 V
外部尺寸 (长 x 宽 x 高)	921 x 348 x 795 mm
重量 (无配件)	95 kg
工作温度范围	-20...+40 °C